



## Key Features

- Accurate and stable temperature measurement for 24/7 monitoring, when higher resolution is not required
- Narrow field of view option for system integrators
- Easy integration to existing IT systems with support for Industrial protocols, such as modbus TCP, EtherNet/IP, MQTT and REST API
- Small and rugged with various connections including: M12 Ethernet, Digital I/O, RS-232/485
- IP66 rated with diamond-like carbon coating on the lens for durability.

## Main Applications

- On-camera analytics and alarm capabilities for condition monitoring and early fire detection
- Quickly access thermal characteristics to catch potential failures, and detect fires before signs of smoke or flames
- Simplify integration efforts with thermal smart sensors that communicate with standard industrial protocols and video management systems

## SPECIFICATIONS

Image and Optical Data	
IR Resolution	320 x 240
Visual Resolution	1280 x 960
Thermal Resolution	29°: <35 mK, 51°: <35 mK, 95°: <35 mK
Focus	Fixed, adjustable with included focus tool
Spatial Resolution (IFOV)	29°: 1.7 mrad/pixel, 51°: 3.0 mrad/pixel, 95°: 5.8 mrad/pixel
FOV Options	29°, 51°, 95°
Detector Pitch	25 μm
Spectral Range	7.5–14.0 μm
Frame Rate	30 Hz
Measurement	
Object temperature range	-20°C to 175°C (-4°F to 347°F) 175°C to 1000°C (347°F to 1832°F)
Accuracy	±2°C (±3.6°F) or ±2% of reading, for ambient temperature 15°C to 35°C (59°F to 95°F) and object temperature above 0°C (32°F)
Measurement Analysis	
Standard Functions	10 Spotmeters, 10 Boxes or Polygons, 3 Deltas (difference any value/reference/external lock), 2 Isotherm (above/below/interval), 2 Iso-coverage, 2 Lines, 1 Polyline, 1 Reference temperature

Specifications subject to change. For the most up-to-date specifications, please visit [flir.com](http://flir.com).



This product is subject to United States export regulations and may require US authorization prior to export, reexport, or transfer to non-US persons or parties. Diversion contrary to US law is prohibited.

For assistance with confirming the Jurisdiction & Classification of Teledyne FLIR, LLC products, please contact [exportquestions@flir.com](mailto:exportquestions@flir.com). ©2024 Teledyne FLIR, LLC. All rights reserved.

Revised 12/18/24  
A40-DATASHEET-LTR 24-0685-INS

Measurement Analysis Continued	
Automatic Hot/Cold Detection	Max./Min. temperature value and position shown within Box
Measurement Frequency	Up to 10 Hz
Measurement Result Read-out	EtherNet/IP (pull), Modbus TCP server (pull), MQTT (push), Query over REST API (pull), Measurements and image (radiometric JPEG, visual 640 x 480, visual 1280 x 960), read access, Web interface
Alarm	
Alarm Function	On any selected measurement function, digital in, and internal camera temperature
Alarm Output	Digital out, e-mail (SMTP) (push), EtherNet/IP (pull), File Transfer (FTP) (push), Modbus TCP Client (push), Modbus TCP Server (pull), MQTT (push), ONVIF events (push), Query over RESTful API (pull), store image or video
Video Streaming, RTSP	
Unicast	Yes
Multicast	Yes
Radiometric RTSP	Compressed JPEG-LS (FLIR Radiometric)
Multiple Image Streams	Yes
Video Stream 0	
Streaming Resolution	640 x 480
Source	Visual / IR / MSX® (*Not available in the 95° version) / FSX®
Contrast Enhancement	FSX® / Histogram equalization (IR only)
Overlay	With/Without
Encoding	H.264, MPEG4, or MJPEG
Video Stream 1	
Streaming Resolution	1280 x 960
Source	Visual
Overlay	No
Encoding	H.264, MPEG4, or MJPEG
Ethernet	
Interface	Wired
Ethernet Connector Types	M12 8-pin X-coded, female
Ethernet Type & Standard	1000 Mbps, IEEE 802.3
Ethernet Power	Power over Ethernet, PoE IEEE 802.3af class 3
Ethernet Protocols	EtherNet/IP, Modbus TCP Server, MQTT, SNMP, TCP, UDP, SNTP, PTP, RTSP, RTP, HTTP, HTTPS, ICMP, IGMP, sftp (server), FTP (client), SMTP, DHCP, MDNS (Bonjour), uPnP

Digital Input/Output	
Connector Type	M12 Male 12-pin A-coded (shared with external power)
Digital Input	2x opto-isolated, Vin (low) = 0 to 1.5 V, Vin (high) = 3 to 25 V
Digital Output	3x opto-isolated, 0 to 48 V DC, max. 350 mA (derated to 200 mA at 60°C). Solid-state opto relay, 1x dedicated as fault output (NC)
Power	
Power Consumption	7.5 W at 24 V DC typical, 7.8 W at 48 V DC typical, 8.1 W at 48 V PoE typical
External Power Operation	24/48 V DC 8 W max
External Voltage	Allowed range 18 V to 56 V DC



PREMIUM  
CHANNEL  
PARTNER

 **CORPORATE OFFICE**

**Hi-Tech Systems & Services Ltd.**

White House, 119 Park Street  
Kolkata 700 016, India

 +91 33 2229 0045  flir@hitech.in  hitech.in

**BRANCHES**

Bhubaneswar	New Delhi
Chennai	Raipur
Hyderabad	Singrauli
Jamshedpur	Vadodara
Mumbai	