

# FLIR ADGiLE™

## Automated Methane Monitoring Solution with Optical Gas Imaging



### Key Features

- Continuous, reliable 24/7 monitoring of methane emission detection with analytics for real-time, accurate results, reducing false positives and unnecessary inspections
- Low-cost, low-maintenance alternative to cooled OGI systems for methane detection, providing operational insight to facilities and effectively supporting environmental initiatives
- Advanced situational awareness so you can accurately distinguish between operational and fugitive emissions to improve safety and production efficiency
- Fixed and pan/tilt options available to ensure compatibility with your specific monitoring needs

### Main Applications

- Provides continuous methane detection to monitor and manage methane emissions effectively in upstream and midstream oil and gas operations
- Ensures real-time methane leak detection at wellpads, gas production facilities and midstream locations
- Ideal for facilities requiring around-the-clock monitoring to identify and mitigate methane leaks promptly

### SPECIFICATIONS

Imaging and optical	
Infrared resolution	320 × 240 pixels
Thermal sensitivity (NETD)	<25 mK at 30°C (86°F)
Gas sensitivity (NECL)	CH <sub>4</sub> : < 100 ppm × m (ΔT = 10°C, Distance = 1 m)*
Field of view (FOV)	25° × 19°
Minimum focus distance	0.3 m (0.98 ft)
Focal length	18 mm (0.71 in)
Spatial resolution (IFOV)	1.4 mrad/pixel
Lens identification	Automatic
f-number	1.04
Image frequency	30 Hz
Focus	Motorized
Detector data	
Focal plane array/spectral range	Uncooled microbolometer/7.0 μm to 8.5 μm
Detector pitch	25 μm
Measurement	
Camera temperature range	Range 1: -20°C to 80°C (-4°F to 176°F) Range 2: 0°C to 250°C (32°F to 482°F) Range 3: 100°C to 500°C (212°F to 932°F)
Accuracy	±3°C (±5°F) for ambient temperature 15°C to 35°C (59°F to 95°F)

Measurement analysis	
Atmospheric transmission correction	Based on inputs of distance, atmospheric temperature, and relative humidity
Lens transmission correction	Automatic, based on signals from internal sensors
Emissivity correction	Variable from 0.01 to 1.0
Reflected apparent temperature correction	Based on input of reflected temperature
External optics/windows correction	Based on input of optics/window transmission and temperature
Measurement corrections	Global object parameters
Power system	
Power consumption	21 W
External power operation	Compatible with IEEE 802.3af, IEEE 802.3at/PoE Plus
External voltage	PoE Class 4 (25 W)
Environmental data	
Operating temperature range	-30°C to 50°C (-22°F to 122°F)
Storage temperature range	IEC 68-2-1 and IEC 68-2-2, -40°C to 70°C (-40°F to 158°F) for 16 hours
Humidity (operating and storage)	Relative humidity: from 5% up to 95%
EMC	EN 55032:2015 Emission Requirements EN 55035:2017 Immunity Requirements FCC – Title 47 CFR Part 15:2019 ICES-001 Issue 4:2014

Specifications subject to change. For the most up-to-date specifications, please visit [www.flir.com](http://www.flir.com).

This product is subject to United States export regulations and may require US authorization prior to export, reexport, or transfer to non-US persons or parties. Diversion contrary to US law is prohibited.

For assistance with confirming the Jurisdiction & Classification of Teledyne FLIR, LLC products, please contact [exportquestions@flir.com](mailto:exportquestions@flir.com). ©2024 Teledyne FLIR, LLC. All rights reserved.

Revised 05/29/24  
ADGiLE-Datasheet-LTR 24-0144-INS



# FLIR ADGiLE™

## Automated Methane Monitoring Solution with Optical Gas Imaging

### SPECIFICATIONS, CONT.

Encapsulation	IP67
Safety	IEC 62368-1 (IT equipment audio-visual products)
Corrosion	Salty fog resistance: ISO9227, to 1000 hours
Declaration of conformity	See: <a href="https://support.flir.com/resources/DoC">https://support.flir.com/resources/DoC</a>
<b>Physical data</b>	
Mounting options	Fixed or pan-tilt
Weight	Fixed: 5.9 kg (13.0 lb) Pan-Tilt: 15.0 kg (33.0 lb)
Size (L x W x H)	510 mm x 177 mm x 229 mm (20.10 in x 6.97 in x 9.02 in)
Housing material	Aluminium
Color	White
<b>Pan-tilt unit</b>	
FLIR PTU-D100E specifications	Fixed solution only. See: <a href="https://www.flir.com/products/ptu-d100e">https://www.flir.com/products/ptu-d100e</a>
<b>Control cabinet</b>	
Weight	20.95 kg (46.18 lb)
Size (external)	510 mm x 177 mm x 229 mm (20.10 in x 6.97 in x 9.02 in)
Size (mounting plate)	535 mm x 430 mm (21.06 in x 16.90 in)
Power input	120 V DC, 50 Hz to 60 Hz 230 V DC, 50 Hz to 60 Hz
Internal power supplies	85 V to 264 V AC / 24 V DC, 3 A (3 power supplies)
Ethernet to serial converter supply	12 V to 48 V DC, 47.3 mA @ 24 V DC
1 + 4 port PoE switch	12 V to 57 V DC, 5.65 A @ 24 V DC
<b>Warranty and service</b>	
Warranty	<a href="http://www.flir.com/warranty/">http://www.flir.com/warranty/</a>

Specifications subject to change. For the most up-to-date specifications, please visit [www.flir.com](http://www.flir.com).



PREMIUM  
CHANNEL  
PARTNER

#### CORPORATE OFFICE

##### Hi-Tech Systems & Services Ltd.

White House, 119 Park Street

Kolkata 700 016, India

+91 33 2229 0045 | [flir@hitech.in](mailto:flir@hitech.in) | [hitech.in](http://hitech.in)

#### BRANCHES

Bhubaneswar      New Delhi


Chennai              Raipur

Hyderabad          Singrauli

Jamshedpur        Vadodara

Mumbai

For more information about  
FLIR ADGiLE, please scan  
or visit:



This product is subject to United States export regulations and may require US authorization prior to export, reexport, or transfer to non-US persons or parties. Diversion contrary to US law is prohibited.

For assistance with confirming the Jurisdiction & Classification of Teledyne FLIR, LLC products, please contact [exportquestions@flir.com](mailto:exportquestions@flir.com). ©2024 Teledyne FLIR, LLC. All rights reserved.

Revised 05/29/24  
ADGiLE-Datasheet-LTR 24-0144-INS