

P/N: 72201-0106

Copyright

© 2025, FLIR Systems, Inc.

All rights reserved worldwide. Names and marks appearing herein are either registered trademarks or trademarks of FLIR Systems and/or its subsidiaries. All other trademarks, trade names or company names referenced herein are used for identification only and are the property of their respective owners.

Document identity

Publ. No.: 72201-0106

Release: AD

Commit: 103167

Language:

Modified: 2025-03-19

Formatted: 2025-03-19



General description

The FLIR K45 is a robust and reliable infrared camera designed to perform under extremely severe conditions. The FLIR K45 has an intuitive interface with a design that makes it easy to control even with a gloved hand. The crisp and clear image helps you to navigate through smoke and to make quick and accurate decisions.

Benefits:

- **Robust and reliable:** The FLIR K45 is designed to meet tough operating conditions. It can withstand a drop from 2 m (6.5 ft.) onto a concrete floor, is water resistant to IP67, and is fully operational up to 60°C (140°F), or 260°C (500°F) for 5 min.
- **Clear and crisp thermal images:** The maintenance-free uncooled microbolometer sensor produces clear and detail-rich images of 240 × 180 pixels which have been further improved with FSX, a digital image processing enhancement technique. Thermal images are presented on a large, bright 4" display, helping you to navigate and to make quick and accurate decisions.
- **Easy-to-use—also in a gloved firefighter's hand:** An intuitive and simple user interface allows you to focus on the job. The FLIR K series can be controlled by just three large buttons on top of the unit. Ideal for a gloved firefighter's hand.

Imaging and optical data

IR resolution	240 × 180 pixels
Thermal sensitivity/NETD	< 40 mK @ +30°C (+86°F)
Field of view (FOV)	51° × 38°
Depth of field	0.84 m to infinity (33 in. to infinity)
Focal length	9 mm (0.35 in.)
Spatial resolution (IFOV)	3.6 mrad
F-number	1.25
Image frequency	60 Hz
Focus	Fixed
Zoom	2× digital zoom

P/N: 72201-0106

© 2025, FLIR Systems, Inc.

#72201-0106; r. AD/103167;

Detector data	
Detector type	Focal plane array (FPA), uncooled microbolometer
Spectral range	7.5–13 μm
Pitch	25 μm
Image presentation	
Display	4 in. LCD, 320 × 240 pixels, backlit
Auto range	Yes, selectable on/off using FLIR K-series camera configurator
Contrast optimization	Digital image enhancement using FSX
Image presentation modes	
Image modes	- IR image - Basic mode - Black and white firefighting mode - Fire mode - Search and rescue mode - Heat detection mode - Thumbnail gallery
Measurement	
Object temperature range	–20°C to +150°C (–4°F to +302°F) 0°C to +650°C (+32°F to +1202°F)
Accuracy	±4°C (±7.2°F) or ±4% of reading, for ambient temperature 10°C to 35°C (+50°F to 95°F)
Measurement analysis	
Spotmeter	1
Automatic hot detection	Heat detection mode (the hottest 20% of the of scene is colorized)
Isotherm	Yes
Set-up	
Set-up commands	Local adaptation of units, date and time formats
Languages	English
Storage of images	
Image storage	Standard JPEG
Storage media	Internal flash memory
Image storage capacity	200 images
Image storage mode	IR only
File formats	Standard JPEG
Video streaming	
Non-radiometric IR video streaming	Uncompressed colorized video using USB
USB	
USB	USB Mini-B
Data communication interfaces	
Interfaces	- Update from PC devices - Data transfer to and from PC

P/N: 72201-0106

© 2025, FLIR Systems, Inc.

#72201-0106; r. AD/103167;

Power system	
Battery type	Li Ion
Battery voltage	3.6 V
Battery capacity	4.4 Ah, at +20°C to +25°C (+68°F to +77°F)
Battery operating time	Approx. 4 hours at +25°C (+77°F) ambient temperature and typical use
Charging system	- Battery is charged inside the camera 2-bay charger - Optional In-truck charger
Charging time	2 h to 85% capacity, charging status indicated by LEDs
Charging temperature	0°C to +45°C (+32°F to +113°F)
Power management	Automatic shutdown and sleep mode
Start-up time from sleep mode	< 4 s.
Start-up time	< 17 s. (IR image, no GUI)
Battery documents	For documents like MSDS and UN38.3 test reports/summaries, see: https://support.flir.com/resources/msds
Environmental data	
Operating temperature range	-20°C to +60°C (-4°F to +140°F) +150°C (+302°F): 15 min. +260°C (+500°F): 5 min.
Storage temperature range	-40°C to +70°C (-40°F to +158°F)
Humidity (operating and storage)	IEC 60068-2-30/24 h 95% relative humidity +25°C to +40°C (+77°F to +104°F) / 2 cycles
Relative humidity	95% relative humidity +25°C to +40°C (+77°F to +104°F) non-condensing
EMC	- EN 61000-6-2:2005 (Immunity) - EN 61000-6-3: 2011 (Emission) - FCC 47 CFR Part 15 B (Emission)
Magnetic fields	EN 61 000-4-8, Test level 5 for continuous field (severe industrial environment)
Encapsulation	IP 67 (IEC 60529)
Shock	25 g (IEC 60068-2-27)
Vibration	2 g (IEC 60068-2-6)
Drop	2 m (6.6 ft.) on concrete floor (IEC 60068-2-31)
Safety (power supply)	CE/EN/UL/CSA/PSE 60950-1
Declaration of conformity	See: https://support.flir.com/resources/DoC
Physical data	
Camera weight, incl. battery	1.1 ±0.05 kg (2.4 ±0.1 lb.)
Battery weight	0.152 kg (0.3 lb.)
Camera size (L × W × H)	120 × 125 × 280 mm (4.7 × 4.9 × 11 in.)
Tripod mounting	UNC ¼"-20 (adapter needed)
Material	- PPSU - Silicon rubber - Aluminium, cast - Flame-resistant magnesium alloy



FLIR K45

P/N: 72201-0106

© 2025, FLIR Systems, Inc.

#72201-0106; r. AD/103167;

Shipping information	
List of contents	• Infrared camera • Battery (2 ea.) • Battery charger • Carabiner strap • Hard transport case • Power supply • Printed documentation • Retractable lanyard, 16 N (58 oz) • USB cable
Packaging, weight	5.7 kg (12.6 lb.)
Packaging, size	500 × 190 × 370 mm (19.7 × 7.5 × 14.6 in.)
EAN-13	4743254002005
UPC-12	845188010898
Country of origin	Estonia

Supplies and accessories:

- 1910423; USB cable Std A <-> Mini-B
- T198509; Cigarette lighter adapter kit, 12 VDC, 1.2 m/3.9 ft.
- T300791ACC; Battery charger, incl. power supply with multi plugs
- T127724ACC; Neck strap
- T198416ACC; Lanyard strap
- T198457ACC; Tripod Adapter, Kxx
- T198441ACC; Transport case Kxx
- T198322ACC; In-truck charger
- T129915ACC; Carabiner strap
- T130980ACC; Retractable lanyard, 16 N (58 oz)
- T300466ACC; Battery locking mechanism replacement kit
- T300815ACC; Battery Li-ion 3.6 V, 4.4 Ah, 16 Wh



PREMIUM
CHANNEL
PARTNER



CORPORATE OFFICE

Hi-Tech Systems & Services Ltd.

White House, 119 Park Street
Kolkata 700 016, India



+91 33 2229 0045




flir@hitech.in




hitech.in

BRANCHES

Bhubaneswar	New Delhi
Chennai	Raipur
Hyderabad	Singrauli
Jamshedpur	Vadodara
Mumbai	





Konstr/Drawn P. MARCUS		Datum/Date 2013-01-23	Kontr/Check -	Material -
Ändrad av/Modified by P. MARCUS		Ändrad/Modified 2013-01-23	Ytlämhet/Roughness Ra	Ytbehandling/Surface treatment µm
Där ej annat anges/Unless otherwise stated Gen tol ISO 2768-mK Utmåg ut/Excerpt from ISO 2768-m		Benämning/Denomination Basic dimension drawing		
0.5-6 (6)-30 (30)-100 (120)-400 (400)-1000		Hållisradier ±0.1 ±0.2 ±0.5 ±0.5 ±0.8		
		Kantler brutna ±0.5 ±0.8		
		Edges broken		
		Sheet/Scale 1:2		
		Blad/Sheet A3		
		Size A3		
		Rev T-127798		



FLIR		Konstr/Drawn P. MARCUS		Datum/Date 2013-01-23	Kontroll/Check -	Material -
Ändrad av/Modified by P. MARCUS		Ändrad/Modified 2013-01-23		Ytbehandling/Surface treatment Ytbehandling/Surface treatment		
Där ej annat anges/Unless otherwise stated		Benämning/Denomination		Skala/Scale 1:2		
Gen till ISO 2768-mK		Utdrag ur/Excerpt from ISO 2768-m		Blad/Sheet 2(2)		
0.5-6		±0.1		A/Nr. A3		
(60)-20		Höjlsradier		Ritning/Drawing No T127798		
±0.2		Fillet radii		Rev		
(120)-400		Kantler brutna				
±0.5		Edges broken				
(400)-1000						

Basic dimension drawing



Konstr/Drawn P. MARCUS	Datum/Date 2013-04-08	Kontr/Check MABR	Material			
Ändrad av/Modified by P. MARCUS	Ändrad/Modified 2013-04-08	Ytjämnhet/Roughness Ra μm	Ytbehandling/Surface treatment			
Där ej annat anges/Unless otherwise stated Gen tol ISO 2768-mK Utdrag ur/Excerpt from ISO 2768-m	Benämning/Denomination Basic dimensions In-truck charger			Skala/Scale 1:5		Blad/Sheet 1(1)
0,5-6 ±0,1 Hålkårsradier (6)-30 ±0,2 Fillet radii (30)-120 ±0,3 (120)-400 ±0,5 Kanter brutna (400)-1000 ±0,8 Edges broken				Art.No.		Size A4
				Ritn nr/Drawing No T127865		Rev A