



## Key Features:

- Wirelessly connects to your smart device for convenient inspections
- Unrivaled thermal image clarity with MSX® (Multi-Spectral Dynamic Imaging)
- Use the Flir One app for efficient thermal analysis, and seamlessly connect to the Flir Ignite™ cloud solution

## Main Applications:

- Identifying and locating moisture intrusion and insulation deficiencies
- Diagnosing issues in HVAC/R inspections
- Identifying abnormalities in electrical and mechanical components

[www.flir.com/flir-one](http://www.flir.com/flir-one)

## Specifications

	Flir Edge	Flir Edge Pro
Thermal resolution	80 x 60 (Native Resolution) 240 x 180 (Super Resolution)	160 x 120 (Native Resolution) 480 x 360 (Super Resolution)
Object temperature range(s)	-20 to 120°C (-4 to 248°F)	-20 to 120°C (-4 to 248°F) 0 to 400°C (32 to 752°F)
VividIR image enhancement	Yes	Yes
Image presentation modes	MSX, infrared image, visual image	
Live measurement analysis	Hottest, coldest, and 3 adjustable spots	
Android & iOS compatibility	Yes, compatible with both iOS and Android devices	
Wireless remote operation	Yes (up to 5 m from smart device)	
<b>General Features</b>		
Device compatibility	iOS (version 15 and later) or Android (version 11 and later) smartphones and tablets	
IP rating	IP54	
Drop tested	Drop from 2 m (6.56 ft)	
Flir software compatibility	Flir One app, Flir Ignite, Flir Thermal Studio	
SDK available for app development	Yes	
Thermal sensitivity	70 mK	
Certifications	RoHS, CE/FCC, CEC-BC, EN62133, UL1642, WEEE 2012/19/EU	
Operating temperature	-10°C to 50°C (14°F to 122°F), battery charging 0°C to 45°C (32°F to 113°F)	

	Flir Edge	Flir Edge Pro
Storage temperature	-40°C to 70°C (-40°F to 158°F)	
Size (w x h x d)	35 mm x 37.5 mm x 149 mm (1.4 in x 1.5 in x 5.9 in)	
Weight (incl. battery)	153 g (5.4 oz)	
Clip span	130 mm (min) / 195 mm (max)	
<b>Optical Data</b>		
Spectral range	8 μm to 14 μm	
Visual resolution	640 x 480	
HFOV / VFOV	54° ±1° / 42° ±1°	
Frame rate	8.7 Hz	
Focus	Fixed 30 cm – infinity	
<b>Measurement</b>		
Accuracy	±3°C (5.4°F) or ±5%. Applicable 60 sec after start-up when the unit is within 15°C to 35°C (59°F to 95°F) and the scene is within 5°C to 120°C (41°F to 248°F)	
Emissivity correction	Matte, Semi-Matte, Semi-Glossy, Glossy	
Measurement correction	Emissivity: Reflected apparent temperature (22°C / 72°F)	
Shutter	Automatic/Manual	
<b>Power</b>		
Battery life	2 h 30 min	
Battery charge time	60–90 min for fully charged. 15 min charging, from empty battery, gives 40 min operating time	

Specifications subject to change. For the most up-to-date specifications, please visit [flir.com](http://flir.com).

For technical or sales support, please visit:

[www.flir.com](http://www.flir.com)

This product is subject to United States export regulations and may require US authorization prior to export, reexport, or transfer to non-US persons or parties. Diversion contrary to US law is prohibited.

For assistance with confirming the Jurisdiction & Classification of Teledyne Flir, LLC products, please contact [exportquestions@flir.com](mailto:exportquestions@flir.com). ©2025 Teledyne Flir, LLC. All rights reserved.

Revised 11/17/25

Flir\_Edge\_Series\_Datasheet\_en-US\_LTR 25-0843-INS



# Flir Edge Series

Thermal cameras with wireless connectivity for iOS® and Android™ smart devices

## Specifications, continued

	Flir Edge	Flir Edge Pro
<strong>Interfaces</strong>		
Wi-Fi	802.11 a/b/g/n	
Bluetooth	Uses Bluetooth to set up the peer-to-peer Wi-Fi network that the camera creates to connect to the mobile device	
Charging	Female USB-C (5V/1A)	
Remote connection	Via Wi-Fi	
<strong>App</strong>		
Video and image capture	Yes	
File formats	Radiometric JPG, MPEG-4 (file format MOV (iOS), MP4 (Android))	
Spot measurements	Hottest, Coldest, and 3 spot measurement	
Adjustable MSX distance	0.3 m – infinity	
Visual battery indicator	0% to 100%	
<strong>Radio</strong>		
Wi-Fi	<ul style="list-style-type: none"><li>Standard: 802.11 a/ac/b/g/n</li><li>Frequency range:<ul style="list-style-type: none"><li>- 2401–2473 MHz</li><li>- 5150–5250 MHz</li></ul></li><li>Max. output power: 15 dBm</li></ul>	
Bluetooth	<ul style="list-style-type: none"><li>Frequency range:<ul style="list-style-type: none"><li>- 2400–2484 MHz</li></ul></li><li>Max. output power: 10 dBm</li></ul>	

Apple Store Flir Apps



Google Play Store Flir Apps



Specifications subject to change. For the most up-to-date specifications, please visit [flir.com](http://flir.com).

For technical or sales support, please visit:

[www.flir.com](http://www.flir.com)

This product is subject to United States export regulations and may require US authorization prior to export, reexport, or transfer to non-US persons or parties. Diversion contrary to US law is prohibited.

For assistance with confirming the Jurisdiction & Classification of Teledyne Flir, LLC products, please contact [exportquestions@flir.com](mailto:exportquestions@flir.com). ©2025 Teledyne Flir, LLC. All rights reserved.

Revised 11/17/25

Flir\_Edge\_Series\_Datasheet\_en-US\_LTR 25-0843-INS