

**MSX® THERMAL CAMERA**

# FLIR TG165-X™

The FLIR TG165-X dramatically reduces inspection and diagnostic time by helping you visually pinpoint the source of electrical, mechanical, and HVAC/R system faults. Instead of searching for temperature anomalies with a single-spot IR thermometer, this non-contact temperature measurement and imaging tool displays a thermal picture of your target including any hot spots or cold zones that could indicate a problem. See wires or components clearly and even read labels thanks to FLIR patented MSX image enhancement, which adds visual details to full thermal images. The bullseye laser helps ensure you're always targeting the right component for measurement while the drop-tested, portable design with easy-to-use buttons and settings help you complete the job quickly and stress-free. With internal storage for up to 50,000 images and rechargeable Li-ion battery, the FLIR TG165-X is ready to go right out of the box.

[www.flir.com/TG165-X](http://www.flir.com/TG165-X)



## PINPOINT THE SOURCE OF SYSTEM FAILURES

Troubleshoot electrical, mechanical, and building issues with this handheld thermal imager

- See temperature anomalies immediately in the thermal image instead of searching for them with a single-spot IR thermometer
- Speed inspections with a thermal view that tells you instantly whether a target has overheating components or hidden air leaks
- Measure a wide range of temperatures, from -25°C to 300°C (-13°F to 572°F), with an accuracy of up to  $\pm 1.5^\circ\text{C}$  ( $\pm 3^\circ\text{F}$ )

## COMPLETE INSPECTIONS QUICKLY & EASILY

See the detail needed to troubleshoot faults and gauge their severity

- Interpret images faster and easier with MSX® two-camera technology, which enhances thermal images with crisp visual details
- Identify the exact area that you're measuring using the bullseye laser pointer
- Capture thermal MSX or visual images plus temperature readings with a simple trigger-pull
- Demonstrate the problem was found and corrected with recorded before-and-after images

## WORK WITH CONFIDENCE

Take the TG165-X anywhere thanks to its portable design and protective IP54 enclosure

- Work safely and worry-free knowing that the thermal imager can withstand a 2-meter drop
- See into dark or hard-to-reach areas with the bright LED worklight
- Easily view live thermal or recorded images on 2.4-in. display
- Rely on the security of the world-class FLIR 2-10 warranty

## SPECIFICATIONS

Imaging and optical data		Storage of images	
IR resolution	80 × 60 pixels	Storage media	4 GB
Digital image enhancement	No	Image storage capacity	50,000 images
Thermal sensitivity/NETD	<70 mK	Image file format	JPEG with spot temp in meta tag
Field of view (FOV)	51° × 66°	Digital camera	
Minimum focus distance	0.3 m (0.98 ft)	Resolution	2 MP (1600 × 1200 pixels)
Distance to spot ratio	24:1	Focus	Fixed
Pseudo dual range	No	Field of view	71° × 56°, adapts to the IR lens
Image frequency	8.7 Hz	Worklight and Laser	
Focus	Fixed	Worklight	LED on/off
Detector data		Light output	100 lumens
Focal plane array/spectral range	Uncooled microbolometer/7.5–14 µm	Bullseye laser pointer	Indicating the size of the measurement area
Detector pitch	17 µm	Laser type	Class 1
Image presentation	<th>Data communication interfaces</th> <td></td>	Data communication interfaces	
Display resolution	320 × 240 pixels	Interfaces	USB 2.0
Screen	2.4 in. portrait, 80° viewing angle	USB standard	USB Type-C High Speed; data transfer/power
Image adjustment	Automatic	Power system	
Image modes	• MSX® (Multi Spectral Dynamic Imaging) • Visual (with temperature reading)	Battery type	Rechargeable Li-ion, 3.7 V battery
Gallery	Yes	Battery operating time	5 hours of scanning (LCM medium brightness) 4.5 hours with laser on (LCM medium brightness)
Measurement and analysis	<td>Battery charge life</td> <td>30 days minimum</td>	Battery charge life	30 days minimum
Object temperature range	-25°C to 300°C (-13°F to 572°F)	Charging system	Battery is charged inside the camera; 4 hrs to 90%, 6 hrs. to 100%
Accuracy	• 50°C to 100°C (122°F to 212°F) - acc. of ±1.5°C (±3°F) • 0°C to 50°C/100°C to 300°C (32°F to 122°F/212°F to 572°F) - acc. of ±2.5°C (±5°F) • -25°C to 0°C (-13°F to 32°F) - acc. of ±3°C (±7°F)	Power management	Adjustable: off, 5 minutes, 15 minutes, 30 minutes
Minimum measurement distance	0.26 m (0.85 ft.)	General	
Spotmeter	Center spot on/off	Operating temperature range	-10°C to 45°C (14°F to 113°F)
Color palettes	Iron, Rainbow, Whitehot, Blackhot, Arctic, Lava	Encapsulation	IP54 (IEC60529)
Set-up		Shock	25 g (IEC 60068-2-27)
Set-up commands	• Local adaptation of units, language, date, and time formats • Screen brightness (high, medium, low) • Gallery, deletion of images	Vibration	2 g (IEC 60068-2-6)
Emissivity correction	Yes: 4 pre-set levels with custom adjustment of 0.1–0.99	Drop test	Designed for 2 m (6.56 ft.)
		Safety	CE/CB/EN61010/UL
		Weight	0.394 kg (13.9 oz)
		Size (L × W × H)	210 × 64 × 81 mm (8.3 × 2.5 × 3.2 in)
		Tripod mounting	UNC 1/4"-20
		Country of origin	Taiwan

Specifications are subject to change without notice. For the most up-to-date specs, go to [www.flir.com](http://www.flir.com)



**CORPORATE OFFICE**  
**Hi-Tech Systems & Services Ltd.**  
 White House, 119 Park Street  
 Kolkata 700 016, India

+91 33 2229 0045 flir@hitech.in hitech.in

### BRANCHES

Bhubaneswar	New Delhi
Chennai	Raipur
Hyderabad	Singrauli
Jamshedpur	Vadodara
Mumbai	



The World's Sixth Sense®